General Printer Configuration for CFC Dot Matrix Printer

1. Go to Devices and Printers Area
2. Right click without selecting any printer(i.e. open area)
3. Click on "Server Properties"
4. Create a New Form for Custom Paper Setting for 10X6 or 9X6
5. Select a Units as English
   If Printer is 80 column then 9X6 (Width 9, Height 6)
   If Printer is 132 column then 10X6 (Width 10, Height 6)
6. Assign a Form Name as "CFC"
7. Click on "Save" button to finish the Custom setting
8. Exit

Printer Configuration for default Printer

1. Select a Default Printer which is installed as Dot Matrix Printer
2. Click on Printer Properties
3. Select a Default Paper size as "CFC" which is created before
4. Also set a Paper Quality a "Draft"
5. Set a Pixels as 140X172 or which is suitable for your printer

Printer Configuration for Browser (Recommended is Mozilla Firebox)

1. Go to File Tab(Alt+F)
2. Click on Page Setup
3. Set a Margin to "0" for all Sides(Top,Right,Left,Bottom)
4. Also set a "Blank" to Header and Footer for all Features
5. Exit
6. Go to File Tab(Alt +F)
7. Click on Printer Menu
8. Set a Defaulter Paper Size as "CFC"
9. Exit
10. Go to File Tab(Alt +F)
11. Click on Print Preview

12. After getting a Printer layout in New Page, the page should shows a 10X6 Page Layout then printer configuration is fine to start the CFC Operation
    Else set a Shrink Fit as 90%

After these configuration still you are facing any issue, Please contact to Mr. Senthil. (This is applicable only for Madurai Region)